

## **SPECIFICATIONS**

Category 6/Class E patch cords are constructed of UTP 24 AWG stranded copper cable and a modular plug at each end. Patch cords are used in all work area outlets and patch panels. Patch cords are wired to be compatible with both T568A and T568B wiring schemes.

## **APPLICATIONS**

- Ethernet 10BASE-T, 100BASE-T (Fast Ethernet), and 1000BASE-T (Gigabit Ethernet)
- 155 Mb/s ATM, 622 Mb/s ATM, 1.2 Gb/s ATM
- Token Ring 4/16
- Voice over internet protocol (VoIP)

## **TECHNICAL INFORMATION**

- **Category 6/Class E performance:** Exceeds ANSI/TIA-568-C.2 Category 6 and ISO 11801 Class E channel requirements at swept frequencies up to 250 MHz Meets ANSI/TIA-568-C.2 and ISO 11801 Category 6 Component requirements at swept frequencies up to 250 MHz PE insulation.
- **Cable diameter:** 0.235 in. (6.0mm) nominal.
- **FCC compliance:** Complies with ANSI/TIA-1096A (formerly FCC Part 68); contacts plated with 50 micro inches of gold.
- **IEC compliance:** Meets IEC 60603-7.
- **PoE compliance:** Supports IEEE 802.3af/802.3at and proposed 802.3bt type 3 and type 4 PoE applications.
- **Safety compliance:** cULus Listed; UL 1863 and CAN/CSA-C22.2 (UL File E129886).
- **RoHS compliance:** Compliant.
- **Flammability rating:** CM rated.

## **KEY FEATURES**

- **100% performance tested:** Confidence that each patch cord delivers specified performance
- **Patented tangle free latch:** Prevents snags and provides easy release
- **Slender strain relief boot:** Provides easy access in high-density applications
- **Identification:** Provides identification of performance level, length, and quality control number for future traceability.
- **Variety of colors and lengths available:** Meets individual length and color-coding requirements

**AVAILABLE SIZES**

- .5 Meter
- 1 Meter
- 2 Meter
- 3 Meter

**AVAILABLE COLORS**

- **Blue**
- **Yellow**
- **Red**
- **Orange**